

# ROTARY CUTTERS ERC SERIES

# TAR RIVER IMPLEMENTS



Front and Rear  
Chain Shielding  
STANDARD!

3 Year  
Gearbox  
Warranty  
Limited



### Specifications:

- ◇ 45 HP Gearbox
- ◇ Shear Pin PTO on 4' - Slip Clutch on 5' & 6'
- ◇ 4' - 12 GA Deck
- ◇ 5' - 11 GA Deck
- ◇ 6' - 9 GA Deck
- ◇ Cat. 1 Hitch w/ Floating Top Link
- ◇ 1 1/2" Cutting Capacity
- ◇ Laminated Wheels & Re-greaseable Hubs
- ◇ Pan Stump Jumper
- ◇ Safety Chain Shields Standard

Designed to help dealers compete with the big box stores, Tar River Implements introduces the ERC Rotary Cutters. These mowers have front & rear chains standard, are built for 20-55 HP tractors and have a 5 Year Gearbox Warranty (1 year on the rest). They come with shear pin or slip-clutch PTOs, cut capacity of 1 1/2", pan-type stump jumpers and in working widths of 4', 5' and 6'.

Model	Working Width	PTO Protection	Min. HP	Weight (lbs)
ERC-4	48"	Shear-Pin	20	411
ERC-5SC	60"	Slip Clutch	25	499
ERC-6SC	72"	Slip Clutch	35	734



Web: [TarRiverMFG.com](http://TarRiverMFG.com)  
 Email: [Sales@TarRiverMFG.com](mailto:Sales@TarRiverMFG.com)  
[Info@TarRiverMFG.com](mailto:Info@TarRiverMFG.com)

DISTRIBUTED BY:



401 Jeffreys Road  
 Rocky Mount, NC 27804  
 Tel: (252) 822-7140  
 Web: [www.BR-Equipment.com](http://www.BR-Equipment.com)  
 Email: [Sales@BR-Equipment.com](mailto:Sales@BR-Equipment.com)

# ROTARY CUTTERS ARC SERIES

# TAR RIVER IMPLEMENTS



The ARC Medium Duty Rotary Cutters are ideal for backfields, trails, and wildlife paths. Heat-treated blades pivot on a heavy-duty stump jumper to protect the gearbox. Safety Chain Guards are standard.



## ARC384

### 72" / 84"

- ◇ Tractor Horsepower 28-65 / 45 - 90 HP
- ◇ Clevis Style Cat 1 / Cat 1 & 2
- ◇ Cutting Height 1.5-9 in. / 3 - 11 in
- ◇ Deck Height 7.5 in. / 9.8 in
- ◇ Cutting Capacity up to 1" / 2"
- ◇ Deck Material Thickness 11 Ga. with 3/16 in. reinforced sides / 10 Ga.
- ◇ Stump Jumper HD 28.5 in. diameter blade pan / HD 32.5" diameter blade pan

The ARC Standard Duty Rotary Cutters are ideal for cutting grass, stalks, and light brush up to 1" thick with ease. The durable heat-treated blades pivot on the 1/8" thick steel stump jumper to protect the cutter from unseen obstacles, avoiding damage to the gearbox and blades. *Optional Equipment—Front Rubber guards, Front and Rear Chain guards.*



## ARC248SP

- ◇ Tractor Horsepower 20-50
- ◇ Cat 1
- ◇ Cutting Height 1.5-9 in.
- ◇ Deck Height 7.5 in.
- ◇ Cutting Capacity up to 1 in.
- ◇ Deck Material Thickness 12 Ga.
- ◇ Stump Jumper 1/8 in. Thick, Round 22.3 in. pan-type
- ◇ Quick Hitch Compatible

Model	Working Width	PTO Protection	Min. HP	Tail Wheels	Weight (lbs.)
<b>ARC248SP</b>	48"	Shear-Pin	18-32	Single	350
<b>ARC260SP</b>	60"	Shear-Pin	20-50	Single	530
<b>ARC260SC</b>	60"	Slip Clutch	20-50	Single	530
<b>ARC272SC</b>	72"	Slip Clutch	25-65	Single	623
<b>ARC372</b>	72"	Slip Clutch	28-65	Single	761
<b>ARC384</b>	84"	Slip Clutch	45-90	Dual	1,100